

# Hyosung 9I

Elevate the branch experience with the industry's most efficient cash recycler.

The Hyosung 9I island drive-up ATM revolutionizes digital branch transformation with state-of-the-art engineering and a wide range of self-service capabilities powered by our industry-leading BlueVerse™ software.



## Feature Highlights

### Advanced Cash Recycling

Reduce operating costs and increase availability

### Innovative Modular Design

Maximize ATM availability and serviceability

### Flexible Configurations

Choose modules that best meet your needs

### Full Denomination Support

with split cassette option



Modular Design



19" Touchscreen



Recycle up to 8 Denominations



100 notes per Transaction



Up to 430mm Note Capacity per Cassette

# Specifications

## Dimensions

- Height: 1,488mm (58.6")
- Width: 1,089mm (42.9")
- Depth: 1,000mm (39.4")
- Weight: 1,071 kg (2,361.2 lbs)

## Environmental Conditions

- Temperature: 32°F ~ 104°F (0°C ~ 40°C)  
Exterior with heater/AC: -31°F ~ 122°F (-35°C ~ 50°C)
- Humidity 25% ~ 85%

## System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™

## Customer Interface

- 19" Landscape LCD Sunlight Viewable Touchscreen
- Card Reader
- NFC Reader
- Audio Jack

## Servicing

- Front Access
- State of health indicators for all modules

## Media Handling

- Recycling/Deposit Module (Presenter Cash Tray)
  - Configurable with up to 4 large recycling cassettes or 8 small recycling cassettes, plus 1 deposit cassette
  - Large Cassette: 430mm capacity<sup>1</sup>
  - Split Cassette: Top 100mm capacity<sup>1</sup>  
Bottom 185mm capacity<sup>1</sup>
  - Deposit Cassette<sup>2</sup>: 430mm capacity<sup>1</sup>
  - Retract Cassette: 50mm capacity<sup>1</sup>
  - Bundle up to 100 notes per withdrawal/ deposit transaction
- Check Acceptor
  - Up to 30 checks per transaction
  - Deposit cassette: 160mm capacity<sup>1</sup>
  - Retract bin: 50 checks
  - OCR E13B/CMC7 capable

## Security

- Safe – CEN3 ExGas
- Cencon Lock
- Alarm (Seismic & heat)
- Security Camera (IP or CCD optional)

## Printer

- 3.1" graphical thermal receipt printer

## Power Supply

- AC 100 ~ 127V ± 10% / 10.0A, 50 ~ 60Hz

## Additional Features

- Lead-through indicator
- Speaker
- Communication – TCP/IP
- Fitness sorting
- Multi-channel communications
- ActiveTeller capable
- Battery backup built in
- Barcode reader
- Palm vein reader (optional)
- ID scanner (optional)
- Heater

Footnotes:

1: Subject to media quality and other variables

2: Deposit cassette configurations:

- 1 Slot: 430mm capacity<sup>1</sup>
- 2 Slots: 65mm / 330mm capacity<sup>1</sup>
- 3 Slots: 65mm / 65mm / 225mm capacity<sup>1</sup>

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

